

PL-32C20D

4-in-1 2MP HD Analog PTZ High Speed Dome



WDR



AWB



PTZ



Day&Night




IP66

Features

- 2.0MP, 20x optical zoom
- IP66-rated protection against dust and rain
- 2D/3D DNR, Digital WDR
- Up to 128 presets, 4 auto scan, 4 tour
- AHD/TVI/CVI/CVBS video output
- Built-in 10 pcs New Array IR LEDs up to 120m

Dimensions



Specifications

| | |
|----------------------|---|
| Model | PL-32C10D |
| Camera | |
| Image Sensor | 1/2.9" 2MP CMOS |
| Efective Pixels | 1920*1080 |
| Image System | PAL/NTSC |
| Video Frame System | 1080P@25fps (PAL); 1080P@30fps (NTSC) |
| IR Distance | 120m |
| Video Output | TVI/AHD/CVI/CVBS |
| Lens | 4.7-94mm |
| Pan | 360° endless |
| Tilt | 0~90° |
| Zoom | 20x optical zoom |
| Preset Speed | 200°/s |
| S/N Ratio | ≥41dB |
| Noise Reduction | 3D DNR |
| Patterns | 4 patterns, time and speed can be set |
| Functions | |
| Main Menu | UTC support based on DVR |
| AGC | Support |
| White Balance | Auto/Manual |
| Day & Night | Auto/Manual |
| Video Setting | Contrast/Sharpness/Color Gain/Video Format/DWDR/DNR |
| Language | Multi-Language |
| General | |
| Casing | Aluminium alloy |
| Ingress Protection | IP66 |
| Operating Conditions | -30°C ~ 60°C / Humidity 0~95°C RH |
| Power Supply | DC24V/ AC24V |
| Net Weight | 4.5kg |

