

All-in-one CCTV DVR Kit-KITDV101

4CH bullet camera & DVR kit

4CH dome camera & DVR kit



Main Features:

- H.264 Compression
- Real time record and playback
- Mobile view (Iphone, Android)
- USB2.0 Interface
- Multi-language supported
- UPNP ,Free DDNS (Build-In Domain)and P2P
- High performance and low illumination color CMOS sensor
- 18 built-in Φ 5mm IR lamps and better night vision effect
- Night vision projection distance up to 10m
- 3.6mm lens as default and 6mm optional
- Auto backlight compensation



HDMI



IR Lamps



BLC



Mobile Surveillance



Video Compression



USB 2.0


DVR Parameter

	Model	ZKD V0401K
System	Main Processor	Industrial embedded micro-controller
	O/S	Embedded linux system
	System Source	Multi-channels recording, playback, operation and USB backup.
Interface	O/S Interface	16 Bit real-color manual, support mouse operation
	Display Frame	1/4 split display
Video	Video System	PAL (625TVL); NTSC(525TVL)
	Preview Resolution	PAL, D1(704×576),CIF(352×288;NTSC,D1(704×480) CIF(352×240)
	Playback Resolution	PAL, CIF(352×288); NTSC, CIF (352×240) PAL, D1(704×576); NTSC, D1 (704×480)
	Code Capacity	4D1@25fps real-time
	Motion Detection	396 (22*18) detection zone in each display frame settable
Audio	Audio Compression	G711A
	Intercom	Support
Video & Playback	Recording Mode	Manual , alarm , motion detection , schedule recording
	Local Playback	Single CH , multi CH (support 8 CH CIF play back at real-time)
	Search Mode	time, calendar, event, channel search
Storage & Backup	Storage Regulation	Audio : 28.8MBit/H & video:25-450MBit/H
	Record Storage	Hard disk and network
	Backup Mode	Network, USB disk, USB CD
Interface	Video Input	4CH BNC, 1.0Vp-p,75Ω
	Video Output	1CH HDMI, 1 CH BNC, 1.0Vp-p,75Ω,1CH VGA output
	Audio Input	4CH RCA, 200-2800mV, 30KΩ
	Audio Output	1CH RCA, 200-3000mV, 5KΩ
	Alarm Input	N/A
	Alarm Output	N/A
	Network Interface	RJ45 10M/100M
	PTZ Control	Yes
	USB Interface	2 USB Interface
	SATA	1 SATA (max to 3T)
General	Power Supply	12V/3A
	Consumption	<10W(Hard disk excluded)
	Working Temperature	0°C-+55°C
	Working Humidity	10%-90%
	Atmospheric Pressure	86kpa-106kpa
	Dimension	30.8*33*7.5mm
	Weight	1.3kg (Hard disk excluded)

Camera Parameter

Model	ZK-SIR291K / ZK-SMD291K
Image Sensor	1/4"CMOS
Pixels	PAL:752Hx582V NTSC:768Hx494V
Horizontal Resolution	600TVL
Min Illumination	0.1Lux/F1.2
System	PAL/NTSC
IR LED	18 built-in ϕ 5 IR lamp
Day / Night Mode	Automatically IR-cut filter
Lens	3.6mm (6mm optional)
SNR	\geq 48db (AGC OFF)
Shutter Speed	1/50 (1/60) ~ 1/120000 seconds
Gamma Correction	0.45
White Balance	Auto
Backlight Compensation	Auto
Sync Mode	Internal synchronization
Video Out Rate	1.0Vp-p at 75 Ω
Power	DC12V
Working Temperature	-10 $^{\circ}$ C ~50 $^{\circ}$ C
Storage Temperature	-20 $^{\circ}$ C ~60 $^{\circ}$ C
Dimensions(mm)	147(L)x69(H)mm
Gross Weight	430g(ZK-SIR291K) / 150g(ZK-SMD291K)

Packing List



(Come kit - 3.9kg) / (Bullet kit - 4.1kg)



ZKTeco Inc.

ZK Mansion, Wuhe Rd, Gangtou, Bantian, Buji Town,
Longgang District, Shenzhen China 518129
Tel: 86-755-8960 2345/46/47/48
E-mail: sales@zkteco.com
www.zkteco.com

Global Offices:

USA: + 1 732-412-6007
EU: +34 916532891
Brazil: +55 31 2515-8326
Thailand: +66-027199154
Mexico: +52-55-52928418

South Africa: +27 12 259 1047
Egypt: +201110444134
Dubai: +971 4 6091 310
India: +91 8123536788
Indonesia: +62 21 2921 8949

Vietnam: +84-0169-5813007
Philippines: +63 90841 18832
Russia: +8 915 178-46-81