

PT-SDC20K9

H.265 High Speed Dome IP Camera



Technical Specifications

Model	PT-SDC20K9
Performance	
Image Sensor	1/2.9" CMOS Sensor
Image Resolution	2.0 Megapixels (1920*1080)
Minimum Illumination	Color: 0.01Lux@F1.2, B&W: 0.001Lux@F1.2 0 Lux with IR
Day & Night	IR-Cut
IR Distance	120m
Focus Mode/ Gain Compensation	AUTO/Manual
White Balance	AUTO, Manual, ATW, Outdoor/Indoor
S/N Ratio	>48dB
Noise Reduction	2D/3D
Lens	4.3-129mm, 30X optional zoom
Pan	360° endless
Tilt	-2° ~ 90°
Zoom	30X optical zoom
Preset Position	255 preset positions
PTZ features	Outage memory function
Video Compression	H.265/H.264
Dual-Stream	Support
WDR	D-WDR
Electronic Shutter	1/25 - 1/10000sec
Network	
Memory function	Network storage MicroSD(Optional)
Support Protocol	TCP/IP, DHCP, DNS, RTP, RTSP, HTTP,PPPOE,FTP
Patterns/Patrol	
Patterns	4 patterns
Patrol	8 patrols
General	
Casing	Camera:Metal(Aluminum Alloy); Color: white
Power Supply	DC12V
Power Consumption	48W MAX
Working Conditions	-40 C ~ +65 C, <90%RH non-condensing
Protection Rating	IP66
Net Weight	4.7kg

Features

- Real-time H.265/H.264 Image Compression
- 2.0 Megapixels, 30X optional Zoom
- Support Android and IOS system
- IP66-rated protection against dust and rain
- Support Onvif 2.0+, Compatible with mainstream NVR/HVR/NVD
- Easy connection and installation

Product dimension figure

